


CONT. 1X WOOD NAILER

GYP. BD. FURRING

COVER COOLER WALL PANELS EXPOSED TO SALES AREA WITH 5/8" GWB ON 1-5/8" METAL STUDS @ 16" O.C. - SECURE METAL STUDS TO FACE OF COOLER WITH CONSTRUCTION ADHESIVE (DO NOT USE SCREW-TYPE FASTENERS INTO COOLER PANELS)

TRIM EDGE AROUND 1G11 DISPLAY DOOR OPENING (HEAD AND JAMB) WITH 18 GA. STAINLESS STEEL TRIM TO MATCH THAT USED ON GLASS DOORS. COORDINATE COLOR W/ NEW DECOR. DEPTH OF TRIM SHALL EXTEND FROM FACE OF GWB AND FIT BETWEEN COOLER PANEL AND CONTINUOUS BLOCKING. SECURE TRIM WITH CONSTRUCTION ADHESIVE.



SEALANT AT SILL

SEALANT

LINE OF STAINLESS STEEL COVERED WOOD BUMPER RAIL BELOW

1G11 REACH-IN GLASS DOOR AND FRAME

4" x 1-1/2" STAINLESS STEEL FRAME - FURNISHED AS PART OF COLD STORAGE ROOM

COLD STORAGE ROOM WALL PANEL

HEAD AND JAMB DETAIL

DATE	DEFENSE COMMISSARY AGENCY DIRECTORATE OF ENGINEERING FORT LEE, VIRGINIA - LACKLAND AFB, TEXAS		DESIGN STANDARD
JUN 2022	TITLE	COLD STORAGE ROOMS 1G11 GLASS DOOR DISPLAY	132126-12
		REF.	
		REV.	