

DESIGN CRITERIA

1. Related Sections: 26 05 00, 27 15 00 and Division 10 Section: Signage.
2. Low-voltage Switches, Buzzers, and Signs: See Division 10 Section: Signage. Provide in the following locations:

SWITCH	BUZZER	SIGN AT SWITCH
Exterior wall adjacent to personnel door that joins the Receiving Loading Dock Ramp (84) and the Receiving Area 36. *	Wall adjacent to the door to the Receiving Manager's Office (35).	RING FOR DELIVERIES
Exterior wall adjacent to personnel door that provides the most direct access for meat delivery personnel.*	In Meat Wrapping Area (55) on wall near door to Meat Manager's Office (57).	RING FOR MEAT DELIVERIES
Exterior wall adjacent to Carryout/Return Vestibule (3).*	Location 1: Rear wall within Customer Service Room (6) Location 2: In Sales Area on wing wall for Vestibule (65B).	RING FOR SERVICE
Exterior wall adjacent to personnel door that provides the most direct means of access for produce delivery personnel.*	In Produce Processing Area (44) on wall next to door to Produce Manager's Office (45).	RING FOR PRODUCE DELIVERIES
In Sales Area, on meat case end panel nearest door utilized by meat service personnel entering sales area.	In Meat Wrapping Room (56), above door leading to Meat Processing (55).	RING FOR CUSTOMER SERVICE
In Sales Area, Produce Sales Area (42), adjacent to service door leading to Produce Processing (44).	In Produce Processing Room (44), above door leading to Produce Chilled Storage (43).	RING FOR CUSTOMER SERVICE

* Use weatherproof switches in these areas.

NOTE: Where more than one buzzer is located in the same room, provide different sounding units. Delivery buzzers shall have a distinctly different sound from customer service buzzers.

END OF SECTION