



FACE OF GWB PARTITION BEYOND

1/2" SOLID SURFACE BACKSPLASH &
SIDESPLASH WITH CLEAR, SILICONE,
NEEDLE-BEAD SEALANT
(CORIAN, NEUTRAL CONCRETE)

AUTOMATIC SENSOR ACTIVATED
FAUCET

1/2" THICK SOLID SURFACE
COUNTERTOP ON 3/4" THICK
SUBSTRATE
(CORIAN, NEUTRAL CONCRETE)

HSS 4" X 2" X 3/16" STEEL TUBE
FASTENED TO FLOOR SUPPORTED,
STEEL TUBE POSTS CONCEALED
WITHIN WALLS

UNDERCOUNTER MOUNT SINK,
ATTACHED W/ MOUNTING CLIPS &
SEALING COMPOUND

ADA COMPLIANT DRAIN PIPE
WRAP, TYPICAL

CERAMIC TILE FLOOR, WALL, AND BASE NOT SHOWN
FOR CLARITY. DIMENSIONS INDICATED ARE TO
CONCRETE FLOOR SLAB AND GWB WALL SURFACES.

DIMENSIONS INDICATED WILL PROVIDE FOR A FINISH
FLOOR COVERING THICKNESS UP TO 1" WITHOUT
VIOLATING ADA BARRIER FREE CLEARANCE
REQUIREMENTS.

| | | | |
|-------|---|--|---------------------------------|
| DATE | DEFENSE COMMISSARY AGENCY DIRECTORATE OF ENGINEERING FORT LEE, VIRGINIA - LACKLAND AFB, TEXAS | | DESIGN STANDARD 064023-06 |
| | JUN 2022 | | |
| TITLE | SOLID SURFACE COUNTERTOP WITH UNDERCOUNTER MOUNT SINK | | |
| | REF. | | |
| | REV. | | |